

**Serie | 4, Wall-mounted canopy  
rangehood, 90 cm, Stainless steel  
DWB97DM50A**



**Box-design hood: performance and  
matching kitchen design bundled in one  
hood.**

- With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality
- **Intensive speed setting with reset:** automatically resets the hood to normal speed setting after 6 min..
- **LED lighting:** for perfect, energy-efficient illumination of the cooktop.
- **Intensive speed setting:** removes strong kitchen odours especially quickly and effectively.
- **TouchSelect control:** quick touch-control selection of desired settings and light.

**Technical Data**

Typology :	Chimney
Approval certificates :	Australia Standards, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	583-912/583-1022
Height of product, without chimney (mm) :	53
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	13.474
Type of control :	Electronic
Maximum output air extraction (m <sup>3</sup> /h) :	454
Boost position output recirculating (m <sup>3</sup> /h) :	499
Maximum output recirculating air (m <sup>3</sup> /h) :	404
Boost position air extraction (m <sup>3</sup> /h) :	739
Number of lights :	2
Noise level (dB) :	65
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242005087594
Connection Rating (W) :	255
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	60; 50
Plug type :	AU plug
Installation typology :	Wall-mounted



4 242005 087594

## **Serie | 4, Wall-mounted canopy rangehood, 90 cm, Stainless steel DWB97DM50A**

### **Box-design hood: performance and matching kitchen design bundled in one hood.**

---

#### **Design**

- For Wall mounted installation
- Box brand design
- Push Button controls for power and light
- 3 power settings plus intensive setting

#### **Operating and power**

- Max. extraction rate: 740 m<sup>3</sup>/h
- Noise min./max. Normal Level: 52/65 dB\*
- 2 x 3W LED Lights
- Dishwasher safe metal grease filters

#### **Technical Information**

- Suitable for ducted or recirculating operation
- For recirculated extraction optional Recirc. kit or clean air kit (accessory) needed
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Appliance (ducted air): 635-965 MM x 900 x 500 mm
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 500 mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with cleanAir module (HxWxD);  
703 x 900 x 500 mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 500 mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney
- 255 W total connected load
- Electrical cable length 1.3 m

**Serie | 4, Wall-mounted canopy rangehood,  
90 cm, Stainless steel  
DWB97DM50A**

