


# Serie | 6, Induction hob, 60 cm, Black PVS675FB5E









- **DirectSelect:** Direct, simple selection of the desired cooking zone, power and additional functions.
- **CombiZone:** More flexibility by combining two cooking zones with even heat distribution, for large roasters, pans and griddle plates.
- PowerBoost: Up to 50% more power for faster heating.
- **ReStart:** if something boils over, the cooktop automatically turns itself off and saves the last selected setting.
- Induction: Fast, precise cooking, easy cleaning and low energy consumption.

## **Technical Data**

Product name/family:

Cooking zone ceramic

Construction type:

Built-in

Energy input:

Electric

Total number of positions that can be used at the same time: 4

Required niche size for installation (HxWxD):

51 x 560-560 x 490-500

Width of the appliance : 606 Dimensions :  $51 \times 606 \times 527$ 

Dimensions of the packed product (HxWxD) (mm):

126 x 753 x 608

Net weight (kg): 12.839 Gross weight (kg): 14.0 Separate Residual heat indicator: Location of control panel: Hob front Basic surface material: Ceramic Color of surface: Black Approval certificates: AENOR, CE Length electrical supply cord (cm): 110 EAN code: 4242005098408 Electrical connection rating (W): 6900 Voltage (V): 220-240 Frequency (Hz): 50; 60





# Serie | 6, Induction hob, 60 cm, Black PVS675FB5E

#### Design

- Stainless steel side trims with bevelled front.

#### Speed

 PowerBoost: rapid heating for large pots of water, automatically turns off right on time to prevent overheating

#### **Comfort & Convenience**

- Combi Induction. Each zone has 2 use options: 2 individual induction cooking zones or combine the front and rear zones together to form one large induction cooking zone
- 4 induction cooking zones
- DirectSelect Touch Controls
- Move function
- Electronic TouchControl display
- Timer with automatic switch off for all zones, Alarm clock
- QuickStart: Quick and automatic first pot detection
- ReStart function
- Automatic pan recognition sensor PowerManagement Function Automatic Safety switch-off Childproof lock WipeProtection

## Size & Power

- Cooking zones:
- 1 x 380 mm x210 mm, 3.6 KW Induction or 2 x 190 mm, 210 mm, 2.2 KW (max. power 3.7 KW) Induction; 1 x  $\varnothing$  145 mm, 1.4 KW (max. power 2.2 KW) Induction; 1 x  $\varnothing$  180 mm, 1.8 KW (max. power 3.1 KW) Induction
- 17 power levels

## **Safety and Environment**


- 2 stage residual heat indicator for each zone
- Spill protection: a built-in overflow container accessed beneath the cooktop that collects any spills that enter the ventilator compartment (can be easily emptied).
- 6.9 KW total connected load


# **Dimensions**

- Installation dimensions: (H/W/D) 51 mm x 560 mm x 490 mm
- Appliance dimensions: (W/D) 606 mm x 527 mm
- Min. worktop thickness: 16 mm




# Serie | 6, Induction hob, 60 cm, Black PVS675FB5E






Measurements in mm



① Ventilation gap must be present.

Measurements in mm



A: Minimum distance from the hob cut-out to the wall.

B: Recessed depth
 C: The clearance between the surface of the worktop and the top of the front of the oven must be 30 mm. See space requirements for the oven.

The worktop into which the hob is installe must withstand loads of approx. 60 kg; suitable substructures must be used if required.

D E F 585-600 50 ≥ 35 > 600 ≥ 50 ≥ 50