

Serie | 6, Heat pump tumble dryer, 8 kg WTR85T00AU









Optional accessories

WMZ20600 : Wool in basket - accessory WTZ27400 : Stacking kit with pull-out shelf

WTZ27410 : Stacking kit

Excellent energy efficiency and Drying performance, Everytime.

- AutoDry saves time and energy by automatically stopping the drying process once it's complete
- Sensitive Drying system combines warm air currents and a gentle drum structure for dry clothes
- **Anti-crease:** laundry is automatically loosened once program finished and does not crease.
- **AntiVibration Design:** extremely stable and especially quiet thanks to special vibration protection.
- **Display for time remaining:** you always know when your laundry will be dry.

Technical Data

Door hinge: Right Length electrical supply cord (cm): 145.0 Height of removable worktop (mm): 842 Dimensions of the product (mm): 842 x 598 x 599 Net weight (kg): 48.603 Fluorinated greenhouse gases: No Type of refrigerant: R290 Hermetically sealed equipment: Yes Quantity of fluorinated gases (kg): 0.120 The quantity expressed in CO2 equivalent (t): 0.000 EAN code: 4242005206988 Connection Rating (W): 1000 Fuse protection (A): 10 Voltage (V): 220-240 Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Built-in / Free-standing :	Free-standing
Length electrical supply cord (cm): 145.0 Height of removable worktop (mm): 842 Dimensions of the product (mm): 842 × 598 × 599 Net weight (kg): 48.603 Fluorinated greenhouse gases: No Type of refrigerant: R290 Hermetically sealed equipment: Yes Quantity of fluorinated gases (kg): 0.120 The quantity expressed in CO2 equivalent (t): 0.000 EAN code: 4242005206988 Connection Rating (W): 1000 Fuse protection (A): 10 Voltage (V): 220-240 Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Removable top:	No
Height of removable worktop (mm): Dimensions of the product (mm): Net weight (kg): Fluorinated greenhouse gases: Type of refrigerant: Hermetically sealed equipment: Quantity of fluorinated gases (kg): The quantity expressed in CO2 equivalent (t): EAN code: Connection Rating (W): Fuse protection (A): Voltage (V): Frequency (Hz): Approval certificates: Capacity cotton (kg) - NEW (2010/30/EC): 842 x 598 x 599 842 x	Door hinge :	Right
Dimensions of the product (mm): Net weight (kg): Fluorinated greenhouse gases: Type of refrigerant: Hermetically sealed equipment: Quantity of fluorinated gases (kg): The quantity expressed in CO2 equivalent (t): EAN code: Connection Rating (W): Fuse protection (A): Voltage (V): Frequency (Hz): Approval certificates: Capacity cotton (kg) - NEW (2010/30/EC): 842 x 598 x 598 482 x 598 x 599 482.603	Length electrical supply cord (cm):	145.0
Net weight (kg): Fluorinated greenhouse gases: Type of refrigerant: Hermetically sealed equipment: Quantity of fluorinated gases (kg): The quantity expressed in CO2 equivalent (t): EAN code: Connection Rating (W): Fuse protection (A): Voltage (V): Frequency (Hz): Approval certificates: Capacity cotton (kg) - NEW (2010/30/EC): 8290 R290 4242005206988 2242005206988 CE, VDE	Height of removable worktop (mm) :	842
Fluorinated greenhouse gases: Type of refrigerant: Hermetically sealed equipment: Quantity of fluorinated gases (kg): The quantity expressed in CO2 equivalent (t): EAN code: Connection Rating (W): Fuse protection (A): Voltage (V): Frequency (Hz): Approval certificates: Capacity cotton (kg) - NEW (2010/30/EC): R290 Ap290 Ap	Dimensions of the product (mm):	842 x 598 x 599
Type of refrigerant: Hermetically sealed equipment: Quantity of fluorinated gases (kg): The quantity expressed in CO2 equivalent (t): EAN code: Connection Rating (W): Fuse protection (A): Voltage (V): Frequency (Hz): Approval certificates: Capacity cotton (kg) - NEW (2010/30/EC): Results Sealed equipment: Yes 4242005206988 2442005206988 220-240 220-240 CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Net weight (kg):	48.603
Hermetically sealed equipment: Quantity of fluorinated gases (kg): O.120 The quantity expressed in CO2 equivalent (t): EAN code: Connection Rating (W): Fuse protection (A): Voltage (V): Frequency (Hz): Approval certificates: Capacity cotton (kg) - NEW (2010/30/EC): Yes A. Yes A. Yes A. Yes A. Yes A. 20.120 A. 20.200 A. 24005206988 A. 2442005206988 A. 2422005206988 A. 242200520698 A. 242200520	Fluorinated greenhouse gases:	No
Quantity of fluorinated gases (kg): 0.120 The quantity expressed in CO2 equivalent (t): 0.000 EAN code: 4242005206988 Connection Rating (W): 1000 Fuse protection (A): 10 Voltage (V): 220-240 Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Type of refrigerant :	R290
The quantity expressed in CO2 equivalent (t): EAN code: Connection Rating (W): Fuse protection (A): Voltage (V): Frequency (Hz): Approval certificates: Capacity cotton (kg) - NEW (2010/30/EC): 0.000 4242005206988 1000 220-240 220-240 CE, VDE	Hermetically sealed equipment :	Yes
EAN code : 4242005206988 Connection Rating (W) : 1000 Fuse protection (A) : 10 Voltage (V) : 220-240 Frequency (Hz) : 50 Approval certificates : CE, VDE Capacity cotton (kg) - NEW (2010/30/EC) : 8.0	Quantity of fluorinated gases (kg):	0.120
Connection Rating (W): 1000 Fuse protection (A): 10 Voltage (V): 220-240 Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	The quantity expressed in CO2 equivalent (t):	0.000
Fuse protection (A): 10 Voltage (V): 220-240 Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	EAN code:	4242005206988
Voltage (V): Frequency (Hz): Approval certificates: Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Connection Rating (W):	1000
Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Fuse protection (A):	10
Approval certificates : CE, VDE Capacity cotton (kg) - NEW (2010/30/EC) : 8.0	Voltage (V):	220-240
Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Frequency (Hz):	50
	Approval certificates :	CE, VDE
Energy officiency rating	Capacity cotton (kg) - NEW (2010/30/EC) :	8.0
Ellergy elliciency facility:	Energy efficiency rating:	A++





Serie | 6, Heat pump tumble dryer, 8 kg WTR85T00AU

Excellent energy efficiency and Drying performance, Everytime.

Capacity

Consumption rates

 8 Energy Stars, Energy consumption 152.0 kWh per year on Cottons, Cupboard Dry Plus, Drying level + 2

Programs

 Cottons Cupboard Extra Dry, Cottons Cupboard Dry, Cottons Iron Dry, Sportswear, Mix, Timed Program Warm, Timed Programe Cold, Wool Finish, Down Wear, Super 40', Shirts/ Blouses15', Iron Dry, Easy Care Cupboard Iron Dry, Easy Care Cupboard Dry, EasyCare Cupboard Extra Dry

Performance

- Noise level: pleasantly quiet at 64dB(A)
- ActiveAir Technology
- Sensitive Drying system combines warm air currents and a gentle drum structure for dry clothes
- Anti-crease cycle 60 min at the end of programme
- Fine-adjustment of drying intensity to customise your preferred level of dryness

Features

- Touch Control buttons: Low heat, less ironing, programme length, start/pause, fine-tuning of drying aim, 24h end time delay
- Stainless steel drum with SoftFlow™ paddles
- LED Display for remaining time and 24 Hr end time delay, programme status indication, special functions
- Buzzer at the end of the programme
- Time delay to select end of time of your wash (1-24 hours) and time remaining indicator

Design

- Glass door
- 38 cm porthole, 175 $^{\circ}$ swing door
- Anti-Vibration Side Panels reduce vibrations and ensure greater stability during the washing and spinning process.

Safety

- Child-proof lock
- Automatic drum stop when door is opened

Technical Information

- 842 mm x 598 mm x 599 mm (652 mm with door frame)



Serie | 6, Heat pump tumble dryer, 8 kg WTR85T00AU

