

### Serie | 8, Heat pump tumble dryer, 8 kg WTX88M20AU









#### **Optional accessories**

WMZ20600 : Wool in basket - accessory WTZ27400 : Stacking kit with pull-out shelf

WTZ27410 : Stacking kit

- AutoDry saves time and energy by automatically stopping the drying process once it's complete
- **AntiVibration Design:** extremely stable and extraordinarily quiet thanks to special vibration protection.
- ComfortDisplay: easy orientation and usability thanks to a big display.
- Sensitive Drying system combines warm air currents and a gentle drum structure for dry clothes
- **Anti-crease:** laundry is automatically loosened once program finished and does not crease.

#### **Technical Data**

Removable top: No Door hinge: Right Length electrical supply cord (cm): 145.0 Height of removable worktop (mm): 842 Dimensions of the product (mm): 842 x 598 x 599 Net weight (kg): 55.313 Fluorinated greenhouse gases: No Type of refrigerant: R290 Hermetically sealed equipment: Yes Quantity of fluorinated gases (kg): 0.149 EAN code: 4242005206247 Connection Rating (W): 1000 Fuse protection (A): 10 Voltage (V): 220-240 Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0 Energy efficiency rating:	Built-in / Free-standing :	Free-standing
Length electrical supply cord (cm):  Height of removable worktop (mm):  Dimensions of the product (mm):  Net weight (kg):  Fluorinated greenhouse gases:  No Type of refrigerant:  R290 Hermetically sealed equipment:  Quantity of fluorinated gases (kg):  EAN code:  Connection Rating (W):  Fuse protection (A):  Voltage (V):  Frequency (Hz):  Approval certificates:  Capacity cotton (kg) - NEW (2010/30/EC):  842 x 598 x 599  842 x 5	Removable top:	No
Height of removable worktop (mm):  Dimensions of the product (mm):  Net weight (kg):  Fluorinated greenhouse gases:  No Type of refrigerant:  Hermetically sealed equipment:  Quantity of fluorinated gases (kg):  EAN code:  Connection Rating (W):  Fuse protection (A):  Voltage (V):  Frequency (Hz):  Approval certificates:  Capacity cotton (kg) - NEW (2010/30/EC):  842 x 598 x 599  842 x 598 x 599	Door hinge :	Right
Dimensions of the product (mm):  Net weight (kg):  Fluorinated greenhouse gases:  No Type of refrigerant:  Hermetically sealed equipment:  Quantity of fluorinated gases (kg):  EAN code:  Connection Rating (W):  Fuse protection (A):  Voltage (V):  Frequency (Hz):  Approval certificates:  Capacity cotton (kg) - NEW (2010/30/EC):  842 x 598 x 599  842 x 598 x 598  842 x 598 x 599	Length electrical supply cord (cm):	145.0
Net weight (kg): 55.313 Fluorinated greenhouse gases: No Type of refrigerant: R290 Hermetically sealed equipment: Yes Quantity of fluorinated gases (kg): 0.149 EAN code: 4242005206247 Connection Rating (W): 1000 Fuse protection (A): 10 Voltage (V): 220-240 Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Height of removable worktop (mm):	842
Fluorinated greenhouse gases:  Type of refrigerant:  Hermetically sealed equipment:  Quantity of fluorinated gases (kg):  EAN code:  Connection Rating (W):  Tuse protection (A):  Voltage (V):  Frequency (Hz):  Approval certificates:  Capacity cotton (kg) - NEW (2010/30/EC):  R290  R290  Approval certificates:  No R290  Au R290  Average  Average  No Average  Ave	Dimensions of the product (mm) :	842 x 598 x 599
Type of refrigerant:  Hermetically sealed equipment:  Quantity of fluorinated gases (kg):  EAN code:  Connection Rating (W):  Fuse protection (A):  Voltage (V):  Yoltage (V):  Approval certificates:  Capacity cotton (kg) - NEW (2010/30/EC):  Results Sealed equipment:  Yes  4242005206247  1000  220-240  500  CE, VDE  8.0	Net weight (kg):	55.313
Hermetically sealed equipment: Quantity of fluorinated gases (kg): 0.149 EAN code: 4242005206247 Connection Rating (W): 1000 Fuse protection (A): Voltage (V): 429005206247 20006 Fuse protection (A): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Fluorinated greenhouse gases :	No
Quantity of fluorinated gases (kg):       0.149         EAN code:       4242005206247         Connection Rating (W):       1000         Fuse protection (A):       10         Voltage (V):       220-240         Frequency (Hz):       50         Approval certificates:       CE, VDE         Capacity cotton (kg) - NEW (2010/30/EC):       8.0	Type of refrigerant :	R290
EAN code : 4242005206247  Connection Rating (W) : 1000  Fuse protection (A) : 10  Voltage (V) : 220-240  Frequency (Hz) : 50  Approval certificates : CE, VDE  Capacity cotton (kg) - NEW (2010/30/EC) : 8.0	Hermetically sealed equipment :	Yes
Connection Rating (W):       1000         Fuse protection (A):       10         Voltage (V):       220-240         Frequency (Hz):       50         Approval certificates:       CE, VDE         Capacity cotton (kg) - NEW (2010/30/EC):       8.0	Quantity of fluorinated gases (kg):	0.149
Fuse protection (A):       10         Voltage (V):       220-240         Frequency (Hz):       50         Approval certificates:       CE, VDE         Capacity cotton (kg) - NEW (2010/30/EC):       8.0	EAN code:	4242005206247
Voltage (V):       220-240         Frequency (Hz):       50         Approval certificates:       CE, VDE         Capacity cotton (kg) - NEW (2010/30/EC):       8.0	Connection Rating (W):	1000
Frequency (Hz): 50 Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Fuse protection (A):	10
Approval certificates: CE, VDE Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Voltage (V):	220-240
Capacity cotton (kg) - NEW (2010/30/EC): 8.0	Frequency (Hz) :	50
	Approval certificates :	CE, VDE
Energy efficiency rating : A+++	Capacity cotton (kg) - NEW (2010/30/EC):	8.0
	Energy efficiency rating:	A+++





## Serie | 8, Heat pump tumble dryer, 8 kg WTX88M20AU

#### **Technical Information**

- Heat pump technology
- Capacity: 8 kg
- 842 mm x 598 mm x 599 mm (652 mm with door frame)
- Noise level: 62 dB (A) re 1 pW

#### **Consumption rates**

- 10 Energy Stars, Excellent Energy Efficiency and Drying Performance

#### **Programs**

- standard programmes: cotton, easy care
- Special programmes: Mixed Load Program, Super 40 minute program, Allergy Plus / Hygiene, Cottons, shirts/blouses, Delicates, towels, Down wear, Sportswear Program, Duvet, Synthetic, Wool, Timed program cold, Timed program warm

#### Performance

- Large LED-Display for remaining time and 24 h end time delay, programme status indication, special functions.
- Touch control buttons: Ready in, Anti-crease 60 min., Anti-crease 120 min., Child lock 3 sec., Power button, Remote Start, Low Heat and Reduced Ironing option, Signal, Start / Reload / Pause, Fine-tuning of drying aim, Drying aim, 24 h Ready in
- Automatic anti-crease cycle (120 minutes)
- Stainless steel drum with SoftFlow™ paddles
- Low Heat option for delicate and synthetic fabrics
- AntiVibration
- Time delay to select end of time of your wash (1-24 hours) and time remaining indicator
- Buzzer to indicate the end of cycle

#### **Convenience and Safety**

- Child lock



# Serie | 8, Heat pump tumble dryer, 8 kg WTX88M20AU



